

ROBUSTLY engineered,

Discover the R-Series Slide-In Truck Mount -

RADICALLY innovative & ready to REVOLUTIONIZE YOUR SURFACE CLEANING and RESTORATION experience

Engineered from decades of realworld experience with every detail tailored to meet the demands of professionals

Crafted for durability and performance, the R-Series Slide-In showcases premium stainless steel construction through out its frame, brackets, supports, heat exchanger and pressure regulator - delivering long-lasting reliability in every component





MACHINE SPECIFICATIONS

Dimensions:

34"W x 48"D x 34"T

Weight: -95Ø LBS

Robust Build:

Stainless Steel Components

Radical Concepts:


LED Digital Display

Revolutionary Design:

(Cabin Heat Discharge System)



- Featuring an innovative single-side service design, this machine offers quick and easy access to the blower, engine and solution pump oil drains, along with a remotely located engine oil filter
- · Commonality of Parts. Zero Hassle. -Blower belt, pump belt, frames - all the same across the board. Simplified service. Maximum uptime.
- Built to Bear the Load. Every Engine. Every Time. - Heavy-duty external bearing supports on all models because your machine shouldn't flinch when the pressure is on.







ROBUST DESIGN **BACKED BY EXPERIENCE**

TIME TESTED CUSTOMER **APPROVED**

REDEFINING TRUCK MOUNT POWER

TRUSTED BY THE PROS. PERFECTED BY *HERO TECH*

	LIGOID
ATIONS	

	SPECIFICATIONS	
	CONSOLE	
COMPONENT	R4SAIR	RS6LIQUIO
ENGINE	KOHLER ECH149 EFT, 2 CYL AR COOLED	PSI 1.8L EFI, 4 CYL LIQUID CDOLED
CALIFORNIA COMPLIANT		
BEARING HOUSING EXTERNAL, GRERSEABLE	YES	
THROTTLE	ELECTRONIC	
CHOKE		
BLOWER	MD PNEUMRTICS 4005	MD PNEUMATICS 5006
FIR FLOW, CFM	388+	588+
BLOWER FILTER	EXTERNAL	
WASTE TANK PRE-FILTER		
PUMP	GENERAL PUMP PEHT2010S ISTRINLESS STEELI	
WORKING PSI	1200	
GPM	48	
STRINLESS STEEL COMPONENTS	FRAME, BRACKETS, SUPPORTS, HEAT EXCHANGER, PRESSURE RE	
DIGITAL DISPLAY INTERFACE	YES	
POWER DISTRIBUTION MODULE		
THROUGH FLOOR EXHRUST		
BATTERY BOX		
1-1/2" VACUUM HOSE	2 - 10 FT	
S. ABCOM HORE	150 FT	
1/4" SOLUTION HOSE	150 FT	
C/W SHUT OFF VALVE		c1.
	FRESH WATER TANKS	
TRINK	MRTERIAL	DIMENSIONS
6 GRLLON	ROTO-MOLD POLYETHYLENE	TH x 0'8 x W'SS
45 GRLLON ISINGLE OR DURL OPTIONI		39'W x 14'D x 28'T
118 GALLON		55'W x 11'0 x 36'T
	WASTE TANKS	
TRNK	MATERIAL	DIMENSIONS
196 GALLON	STANLESS STEEL	41"W x 15"D x 44"T SS"W x 16"D x 44"T WITH WATER BOX TRAY
199 GALLON	ROTO-MOLD POLYETHYLENE	SEW X 16-D X 43-T WITH WATER BOX TRAY

COMPONENT BREAKDOWN



PSI 1.0L EFI, 4 CYL

- · 38 HP
- CARB/EPA Compliant (50 States)
- Liquid-Cooled
- High Power Density with Fuel Efficiency



MD Pneumatics 5006 Blower

- Tri Lobe
- **Helical Gears**
- 500 + CFM
- Dual Wand Compatible



General Pump PEHT2010S Pump

- Stainless Steel
- 4.0 GPM
- 1.200 PSI
- Last Step Chemical Piston Injection Pump



LED Digital Display

- · IP67 Rating
- Simplified Operation
- Service Reminders
- EFI Trouble Shooting System Updates And More...

